131-175 **ALTO**®

MANSFIELD®

Round Front, Vitreous China, Two-Piece Toilet

FEATURES

- 3-bolt SmartFasten[™] tank-to-bowl connection
- 1.6 gpf / 6.0 lpf low water consumption
- Round front bowl
- · 2' flush tower
- · Anti-siphon ballcock
- 10' rough-in
- · Cover lock tank lid
- · Lined tank for reduced condensation
- · Model 40 chrome-plated, plastic trip lever
- · 2' glazed trapway
- · The Mansfield® Limited Lifetime Warranty
- · Available in White



COMPONENTS

MODEL #	DESCRIPTION	CODES/STANDARDS		
131-175	Round front, two-piece toilet.			
131	Round front, toilet bowl only. Less toilet seat. Specify color.	UPO		
175	nk and cover only with left hand, front-mount, chrome-plated, astic trip lever. Tank liner and cover lock. Less supply.			
TANK TRIM & REPLACEMENT PARTS				
40	Trip lever - chrome-plated, plastic trip lever, left hand			
211-1112	Flush tower			
08ULF-1112	Anti-siphon ballcock			
630-0030	Replacement flush valve seal			
165-LID	Tank lid (cover lock)			
Part # 001238891	Locking hardware for cover lock tanks			



MANSFIELD®

Round Front, Vitreous China, Two-Piece Toilet

SPECIFICATIONS

MODEL #	DESCRIPTION	CODES/STANDARDS
131-175	Round front (1.6 gpf / 6.0 lpf) two-piece toilet	C ®

	T
MATERIAL	Vitreous China
WATER PRESSURE RANGE	20 to 80 PSI
FLUSH SYSTEM	2' Flush Tower
WATER USAGE	1.6 gpf / 6.0 lpf
WATER SURFACE AREA	8' X 9'
ROUGH-IN	10'
MAP RATING	800 grams


TRAP DIAMETER	2'
TRAP SEAL	2-1/4'
SHIPPING WEIGHT	Model 131 - 47 lbs. (21 kg) Model 175 - 34 lbs. (15 kg)
WARRANTY	Vitreous China - Limited Lifetime Tank Trim - Limited One Year

TANK OPTIONS

TECHNICAL INFORMATION

Note: these dimensions are nominal and subject to change without notice.

TANK OPTIONS				
160	Standard 1.6 gpf configuration: 2" flush tower, anti-siphon ballcock, left hand, chrome trip lever.			
160RH	Variation of model 160, with right hand trip lever.			
161	Variation of model 160, with Fluidmaster® antisiphon pilot fill valve.			
165	Variation of model 160, with cover lock.			
170	Variation of model 160, with tank liner.			
172	Variation of model 160, with Fluidmaster® antisiphon pilot fill valve, 2" flapper and chrome trip lever.			
173	Variation of model 160, with Fluidmaster® antisiphon pilot fill valve, 2" flapper and color-match trip lever.			
173RH	Variation of model 173, with right hand trip lever.			
174	Variation of model 173, with tank liner.			
175	Variation of model 160, with cover lock and tank liner.			
180	Variation of model 160, with color-match trip lever.			
181	Variation of model 160, with Fluidmaster® antisiphon pilot fill valve and color-match trip lever.			
190	Variation of model 160, with color-match trip lever and tank liner.			



Fixture performance and specifications meet or exceed ASME A112.19.2/CSA B45.1 standards, and other state and local codes.

