144-155RH **QUANTUM® 1.28**

MANSFIELD®

Elongated Front, Pressure-Assist, Rear Outlet, Wall-Mount, Vitreous China Two-Piece Toilet

FEATURES

- · High performance pressure-assist, high efficiency toilet (HET)
- 1.28 gpf / 4.8 lpf high efficiency water consumption
- Uses 20% less water than conventional toilets
- · Elongated rear outlet, wall-mount
- · Model 49RH chrome-plated metal trip lever
- · 2' glazed trapway
- The Mansfield® limited lifetime warranty on china, Flushmate ten-year limited warranty on vessel
- · Available in White



COMPONENTS

MODEL #	DESCRIPTION	CODES/STANDARDS		
144-155RH	Elongated front, rear outlet, wall-mount pressure-assist, two-piece toilet. Includes tank trim and chrome-plated metal trip lever. Less toilet seat and supply.			
144	Elongated front, rear outlet, wall-mount toilet bowl only. Less toilet seat and supply.	Upo L steerson		
155RH	Pressure-assist tank and cover only with right hand chrome-plated, metal trip lever. Less supply. Specify color.	HIGH EFFICIENCY ADA COMPLIANT ADA COMPLIANT ADA COMPLIANT		
TANK OPTIONS				
155	Pressure-assist tank and cover only with left hand chrome-plated, metal trip lever. Less supply. Specify color.			
TANK TRIM & REPLACEMENT PARTS				
49RH	Trip lever - chrome-plated, metal trip lever, right hand			
125-LID	Tank lid			
FLUSHMATE® 503	Pressure-assist flushing system. Separate warranty applies. Contact FLUSHMATE® at 1-800-533-3460.			

When properly installed, this product meets the requirements for the Americans with Disabilities Act of 1990 (ADA). Refer to local plumbing codes, as they may vary by location and application.

144-155RH **QUANTUM® 1.28**

MANSFIELD®

Elongated Front, Pressure-Assist, Rear Outlet, Wall-Mount, Vitreous China Two-Piece Toilet

SPECIFICATIONS


MODEL #	DESCRIPTION	CODES/STANDARDS
144-155RH	Elongated front, rear outlet, wall-mount (1.28 gpf / 4.8 lpf) two-piece toilet	HIGH EFFICIENCY ADA COMPLIANT ADA COMPLIANT ADA COMPLIANT

MATERIAL	Vitreous China
WATER PRESSURE RANGE	35 to 80 PSI
FLUSH SYSTEM	Flushmate™ flushing technology
WATER USAGE	1.28 gpf / 4.8 lpf
WATER SURFACE AREA	9-3/4' X 8'
ROUGH-IN	Rear outlet, wall mount
MAP RATING	Pending

TRAP DIAMETER	2'
TRAP SEAL	2-1/8'
SHIPPING WEIGHT	Model 144 - 61 lbs. (27.6 kg) Model 155RH - 41 lbs. (18.5 kg)
WARRANTY	Vitreous China - Limited Lifetime Vessel - Limited Ten Year (Flushmate)

TECHNICAL INFORMATION

Note: these dimensions are nominal and subject to change without notice.



When properly installed, this product meets the requirements for the Americans with Disabilities Act of 1990 (ADA). Refer to local plumbing codes, as they may vary by location and application.

Fixture performance and specifications meet or exceed ASME A112.19.2-2013/CSA B45.1-13 standards, and other state and local codes.