




# Designer Collection Shower Bases

## MTSB-6042BF



60" x 42" x 2.25" (exterior bottom of base)
BARRIER-FREE THRESHOLD textured floor
Center Drain
Acrylic CXL®
115 lbs / 52 kg



Designed to be recessed into floor, to create a flat transfer surface.

Not for use in steam shower applications.

Model #	Package Content	Size	Shape	MSRP
SB6042BF	Natural stainless steel drain and channel cover, PVC drain kit	60" x 42" x 2.25"	Rectangle	<b>\$2,605</b>

Options <i>Must be ordered at time of purchase</i>
<b>Color</b> Please specify color on order White (CWH) Biscuit (CBS)
<b>Quick Ship (QSPRI) \$450</b> Reduces lead time. Please call for availability.
<b>Radiance® (RAD100) \$1,675</b> Shower floor heating system. Radiance heating grids are fully integrated within the acrylic shell structure of the shower floor. Requires a 110-volt, 15 amp GFCI and remote installation of control box & keypad.
<b>Pre-Levelled Foam Base (PLFSB) \$230</b>
<b>Drain &amp; Channel Cover</b> Natural stainless steel drain & channel installed on base as standard. Substitute with the following available options: Powder Coated White Stainless Steel Hidden Drain Cover (DCT60W) Must specify part code on order; comes in lieu of standard cover.

Accessories
<b>Drain Kit</b> Solid Brass Drain Kit with Stainless Steel Cover (SBDKSB) <b>\$205</b>
<b>Teak Shower Seat</b> Premium Natural Stainless (TK-SSEAT2416BNS) <b>\$3,125</b> High-Polished Stainless (TK-SSEAT2416BHP) <b>\$3,570</b> Premium ADA Natural Stainless (TK-SSEAT2416BNSA) <b>\$3,740</b> High-Polished Stainless (TK-SSEAT2416BHPA) <b>\$4,155</b> Standard Natural Stainless (TK-SSEAT2215NS) <b>\$1,160</b> High-Polished Stainless (TK-SSEAT2215HP) <b>\$1,620</b>

### IMPORTANT ORDERING & INSTALLATION INFORMATION

- Zero-barrier single front threshold designed for ease of transfer between bathroom and shower area.
- 3-sided integral tile flange to facilitate installation.
- 3.5" drain opening pre-drilled.
- Compliant with ASTM C 1028-07 coefficient of friction test.
- Add proper wet-bedding compound to fully support bottom of shower base. Optional factory installed Pre-Levelled Foam Base negates the need to wet bed when installing on a flat, level subfloor. See installation instructions.

- Options and accessories may be packaged inside the box. Always check packaging before discarding.
- All product measurements are ±1/2".
- Specifications and configurations are subject to change without notice.
- Measurements herein supersede all others published prior to publication date below.

See the Installation & Operation Manual for more details.  
MTI's Customer Service: Monday-Friday 8am-6pm EST  
**800-783-8827** or [service@mtibaths.com](mailto:service@mtibaths.com)

CSA # MTSB-6042BF

©2024 by MTI Baths, Inc. Modification Rights Reserved



Rev. 04 30 2024