



H-7x71 Series

Magnetic Boiler Filter

12,000 Gauss Magnet, Diverter & G1 Union Connections

Integrated Hose Drain Valve, Air Vent & Filter

with (2) G1 Isolation Valves (Includes Service Tool)



NO.	DESCRIPTION	MATERIAL
1	Magnet Stick	Magnet
2	O-ring	Rubber
3	Magnet Cover	Nickel Plated Brass
4	Upper Half of Body	Plastic
5	Plastic Screen Filter	Plastic
6	O-ring	Rubber
7	Lower Half of Body	Plastic
8	Injector	Brass
9	O-Ring	Rubber
10	Drainer	Brass
11	Drainer Stem	Brass
12	Drainer	Brass
13	Rubber Ring	Rubber
14	Cap	Brass
15	Gasket	Rubber
16	Drainer	Brass
17	Valve Ball Seat	Teflon
18	Valve Ball	Brass
19	Vent Valve	Brass
20	O-Ring	Rubber
21	O-Ring	Rubber
22	Diverter Clip Ring	Stainless Steel
23	Diverter	Brass
24	Diverter Nut	Brass
25	Spanner	Plastic

Designed for residential, commercial or industrial use with water or a glycol mixture.

ITEM#	Connection Type	SIZE (in)	Pressure Rating	Max Temp	A
H-72713	FIP	3/4	175 PSI CWP Max	250°F Max	12.96
H-72714	FIP	1	175 PSI CWP Max	250°F Max	13.08
H-74713	MIP	3/4	175 PSI CWP Max	250°F Max	13.28
H-74714	MIP	1	175 PSI CWP Max	250°F Max	13.36
H-75713	SWT	3/4	175 PSI CWP Max	250°F Max	13.24
H-75714	SWT	1	175 PSI CWP Max	250°F Max	13.58
H-78713	Press	3/4	175 PSI CWP Max	250°F Max	14.82
H-78714	Press	1	175 PSI CWP Max	250°F Max	14.82



