




H-86x6 Pro-Pal Multi-Port Tee

H-86x6W Series

Pro-Pal Multi-Port Tee

Forged DZR Brass Tee
w/ 3 Branch Connections
& Press Port Plug



Certifications

Certified to NSF/ANSI 61 & 372
NSF/ANSI 14, CSA B137.5



	Size (in)	Item#	Max Temp	Pressure Rating	Weight (lbs)	Carton Qty	Case Qty
Press Run x F1807 PEX	3/4"	H-86163W	250°F Max	250 PSI CWP	0.85	4	24
	3/4" x 1/2"	H-86163W-R	250°F Max	250 PSI CWP	0.86	4	24
	1" x 3/4"	H-86164W-R	250°F Max	250 PSI CWP	1.04	4	24
Press Run x F1960 PEX	3/4"	H-86363W	250°F Max	250 PSI CWP	0.93	4	24
	3/4" x 1/2"	H-86363W-R	250°F Max	250 PSI CWP	0.90	4	24
	1" x 3/4"	H-86364W-R	250°F Max	250 PSI CWP	1.14	4	24



	Size (in)	Item#	A	B	C	D	E	F
Press Run x F1807 PEX	3/4"	H-86163W	8.09	6.06	1.97	1.97	2.19	1.34
	3/4" x 1/2"	H-86163W-R	8.09	6.06	1.97	1.97	2.19	1.34
	1" x 3/4"	H-86164W-R	8.25	6.22	2.05	1.97	2.27	1.46
Press Run x F1960 PEX	3/4"	H-86363W	8.09	6.06	1.97	1.97	2.19	1.65
	3/4" x 1/2"	H-86363W-R	8.09	6.06	1.97	1.97	2.19	1.42
	1" x 3/4"	H-86364W-R	8.25	6.22	2.05	1.97	2.28	1.77

Specifications: PEX end dimensions comply with the referenced ASTM specification. Designed for use with water, oil, glycol mix in residential or commercial plumbing and heating systems.

NO.	DESCRIPTION	MATERIAL
1	Body	Lead-Free DZR Brass
2	O-Ring	EPDM
3	Plug	Lead-Free DZR Brass

