
THE FLOW®

Quarter-Turn Boiler Drains

125 lb. CWP to 100°F **Maximum Temperature 180°F**


QUARTER-TURN BOILER DRAINS MATERIAL LIST

PART	SPECIFICATION				
Screw	Steel				
I.D. Tag	Aluminum				
Handle	Zinc				
Stem	Brass ASTM B 16 UNS C36000				
O-Ring	Nitrile				
Seat	PTFE				
Ball	Brass ASTM B 16 UNS C36000				
Adapter	Brass ASTM B 283 UNS C37700				
Body	Brass ASTM B 283 UNS C37700				



DESCRIPTION	NOM. Size	DIMENSIONS		APPROX.
		Α	В	NET WT.
BOILER DRAIN FIP to Hose	1/2	2.64"	1.57"	.42 lb
	3/4	2.72"	1.65"	.46 lb

IAPMO Listed to cUPC®



DESCRIPTION	NOM. SIZE	DIMENSIONS		APPROX.
		Α	В	NET WT.
BOILER DRAIN Cup or MIP Threads to Hose	1/2"	2.64"	1.57"	.40 lb
	3/4"*	2.72"	1.65"	.42 lb

IAPMO Listed to cUPC®



WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

^{*} ¾" furnished in male threads only