

Lead-Free Three Piece Bronze Ball Valves

Features: Silicon Performance Bronze® Alloy • Three-Piece Body • Full Port • Blowout-Proof Stem

Approvals: MSS SP-110 • NSF/ANSI-61-8 Commercial Hot 180°F (includes annex F and G) and NSF/ANSI-372

Size range: 1/4" - 2-1/2"

Pressure rating: 600 PSI non-shock cold working pressure

Maximum pressure / temperature: 100 PSI at 300° F

Lead-free markings: Double oval in body casting, white handle and blue hang tag




NSF/ANSI 61
NSF/ANSI 372



MATERIAL LIST


PART	SPECIFICATION
1. Handle	Steel, Plated Plastisol Coated
2. Handle Nut	Zinc Plated Steel
3. Stem	Silicon Bronze ASTM B371 Alloy C69300
4. Threaded Pack Gland	Brass ASTM B16 Alloy C36000
5. Packing	PTFE
6. Thrust Washer	Reinforced PTFE
7. Body Bolts	Zinc Dichromate Plated Steel ASTM A449 Grade 5
8. Body End (2)	Silicon Bronze ASTM B584 Alloy C87850
9. Ball	Silicon Bronze ASTM B283 Alloy C69300 or Stainless Steel ASTM A276 Type 316
10. Body	Silicon Bronze ASTM B584 Alloy C87850
11. O-Ring Seal (2)	FKM
12. Seat Ring (2)	PTFE
13. Body Nuts	Zinc Dichromate Plated Steel ASTM A449 Grade 5
14. Handle Sleeve	Zinc Plated Steel

Note: valves are static grounded by a grounding washer. (Not Shown)





T-595-Y-LF
Threaded


S-595-Y-LF
Solder




Handle Markings



T-595-Y-LF
NPT x NPT



S-595-Y-LF
C x C



Extended Handle
Representation for Suffix -EL

DIMENSIONS—WEIGHTS—QUANTITIES

Size	Dimensions										w/ Extended Handle		E	F	T-595-Y-LF	S-595-Y-LF	Master							
	T-595-Y-LF		S-595-Y-LF		B	C	D	D	E	E	F	Lbs.						Kg.	Lbs.	Kg.	Ctn.	Qty.		
In.	mm.	In.	mm.	In.									mm.	In.	mm.	In.	mm.						In.	mm.
1/4	8	2.50	64	1.69	43	1.81	46	.38	10	1.69	43	2.80	71	3.82	97	3.91	99	1.13	29	1.03	.47	.89	.40	50
3/8	10	2.50	64	1.81	46	1.81	46	.38	10	1.69	43	2.79	71	3.82	97	3.91	99	1.13	29	.98	.44	.89	.40	50
1/2	15	2.50	64	2.06	52	1.81	46	.50	13	1.69	43	2.79	71	3.82	97	3.91	99	1.13	29	1.03	.47	.89	.40	50
3/4	20	3.00	76	2.94	75	1.94	49	.75	19	2.00	51	3.13	79	3.82	97	4.66	118	1.44	37	1.70	.77	1.59	.72	30
1	25	3.69	94	3.66	93	2.50	64	1.00	25	2.25	57	3.32	84	3.82	97	4.66	118	1.84	47	2.82	1.28	2.55	1.15	20
1 1/4	32	4.09	104	3.91	99	2.69	68	1.25	32	2.75	70	3.83	97	5.45	138	6.69	170	1.97	50	3.96	1.80	3.61	1.64	10
1 1/2	40	4.56	116	4.60	117	3.00	76	1.50	38	2.97	75	4.06	103	5.45	138	6.69	170	2.38	60	5.68	2.57	5.31	2.41	10
2	50	6.16	156	5.78	147	4.00	102	2.00	51	3.63	92	4.30	109	5.45	138	6.69	170	3.06	78	11.40	5.17	10.60	4.81	4
2 1/2	65	6.84	174	6.94	176	5.00	127	2.50	64	4.09	104	5.51	140	8.03	204	8.00	203	4.00	102	21.07	9.56	19.30	8.75	2



WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

LEAD-FREE: Weighted average lead content ≤ 0.25%