

The clean, contemporary shape complements any kitchen design. Impressive lighting and superior smoke and odor removal are a mere introduction to everything this hood has to offer.

SIZE	BLACK	WHITE	STAINLESS	GREASE FILTERS (replacement)	NON-DUCTED FILTERS
24 in.		BCS324WWC	BCS324SSC	HPFAMM24 (Type B1)	HPF24 (Type Xb)
30 in.	BCS330BLC	BCS330WWC	BCS330SSC	HPFAMM30 (Type C1)	HPF30 (Type Xc)

PERFORMANCE								
D. al O de alalla	Size	Damper	Sones		CFM			
Duct Orientation			Normal	High	Normal	High		
Vertical - Rectangular	3¼ in. x 10 in.	Included	1.5	5.0	140	230		
Horizontal - Rectangular	3¼ in. x 10 in.	Included	1.5	5.0	110	210		
Round - Vertical	7 in.	Sold Separately	1.5	5.0	150	250		

FEATURES					
Control type	2-speed Rocker				
Delay off	no				
Filter Clean Reminder	no				
Heat Sentry™	no				
ADA Capable	yes				
Lighting	2-level 50 W Halogen (bulbs not included)				
Grease Filters	Micro Mesh (Qty. 2)				
Installation Hardware	Standard				
ENERGY STAR®	no				
Recirculation	Non-ducted filters sold separately				

AC INPUT

120 V, 60 Hz - 1.4 AMPS

OPTIONAL ACCESSORIES					
7-in. Round Damper	BP87Q				
7-in. Round Adapter Plate	SR680508				
Make-up Air Dampers	MD6TU, MD8TU and MD10TU				

MOUNTING HEIGHT

18 in. to 24 in. from cooktop to bottom of hood

LIMITED WARRANTY


1-year

- BCS3 SERIES

SPECIFICATION SHEET

FOR INDOOR USE ONLY 0.5 Vertical High Speed, 7-in. round (ig) 0.4 Vertical High Speed, o.3 (in. v with 3½ in, x 10 in, damper Horizontal High Speed, pressur 0.0 Static 1:0 0 50 100 250 300 350 150 200 Airflow (cfm)









HVI-2100 CERTIFIED RATINGS comply with new testing technologies and procedures prescribed by the Home Ventilating Institute, for offthe-shelf products, as they are available to consumers. Product performance is rated at 0.1 in. static pressure, based on tests conducted in AMCA's state-of-the-art test laboratory. Sones are a measure of humanly-perceived loudness, based on laboratory m