

Under-Cabinet

GLACIER

The clean, contemporary shape of Glacier complements any kitchen design. Impressive LED lighting and superior smoke and odor removal are a mere introduction to everything this hood has to offer. The LED modules included with this hood are the latest in LED cooktop illumination technology specially designed to operate in the elevated temperatures of cooking - offering bright lighting and lasting up to 25 times as long as a standard bulb and greater reliability than typical replacement LED bulbs.

SIZE	WHITE	BLACK	STAINLESS	; G	GREASE FILTERS (replacement)			NON-DUCTED FILTERS	
30 in. BCDA130WW		BCDA130BL	BCDA130S	6 HPFAMM30 (Type C2)			HPF30		
PERFO	RMANCE								
					Sones			CFM	
Duct Orientation		Size	Damper	Normal Medium High		Normal Medium High			
/ertical ·	- Rectangular	3¼ in. x 10 in.	Included	1.5	3.0	5.0	140	180	230
Horizont	al - Rectangular	3¼ in. x 10 in.	Included	1.5	3.0	5.0	110	150	210
Round -	Vertical	7 in.	Sold Separately	1.5	3.0	5.0	150	190	250
EATUR	RES						11		
Control type		3-speed Capacitive Touch							
Delay off		no							
Filter Clean Reminder		yes							
Heat Sentry™		no					(8-4)		
ADA Capable		yes							
Lighting		2-level LED (included)							
Grease Filters		Micro Mesh (Qty. 2)							
Installation Hardware		EZ1 bracket							
ENERGY STAR®		no			I				
Recirculation		Non-ducted filters sold separately							ALL
AC INP	UT			0					Mart
120 V, 6	60 Hz - 0.65 AMF	pS				35	-		- CARL
	AL ACCESSOR	IES				THE LEASE	CERTIFIC CONT	Wild at the California	
7-in. Round Damper		BP87Q		Chine-	to a serie to				
7-in. Round Adapter Plate		e SR680508							
Nake-up Air Dampers		MD6TU, MD8							
MOUNT	ING HEIGHT								
	24 in. from cook	top to bottom of	hood						
	O WARRANTY								
1-year									
3-year (LED modules only								
See ins	tallation manual ťo	or full warranty te	ext.)						
OR IN	DOOR USE ONL	Y					\bigwedge	\sim	
0.5						. /	$\langle \rangle$ *	5 ON 12-0	`
			ertical High Speed, -in. round			`}//	> , >	<u>~</u> ~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	$\langle \rangle$
0.4			ertical High Speed,		~~~//	$\langle \rangle$		- Inl	8
0.3			ith 3¼ in. x 10 in. damper		\swarrow	~	\sim	13 32	1
0.2			orizontal High Speed, ith 3¼ in. x 10 in. damper	F	\sim	710	\mathbf{S}	8	
0.3				\searrow	$\langle \rangle$			/ /	-
0.1							5-1	5*	
0				h.			298	/	
0	50 100	150 200	250 300 350		195		238		ensions

Dimensions shown in inches.



HVI-2100 CERTIFIED RATINGS comply with new testing technologies and procedures prescribed by the Home Ventilating Institute, for offthe-shelf products, as they are avaialable to consumers. Product performance is rated at 0.1 in. static pressure, based on tests conducted in AMCA's state-of-the-art test laboratory. Sones are a measure of humanly-perceived loudness, based on laboratory measurements. 99045733D

SPECIFICATION SHEET GLACIER – BCDA1 SERIES