

Broan brings you a bold new shape in a pro-style hood. The combination of high performance blower, deep canopy design and hybrid baffle filtration will satisfy even the most demanding cooks.

SIZE	STAINLESS	GREASE FILTERS (replacement)	NON-DUCTED FILTERS
30 in.	BPDC130SS	HPFA424 (Type B5)	HPF24 (Type Xb)
36 in.	BPDC136SS	HPFA430 (Type C5)	HPF30 (Type Xc)

PERFORMANCE							
Devet Orientation	Size	Damper	Sones		CFM		
Duct Orientation			Normal	High	Normal	High	
Vertical - Rectangular	3¼ in. x 10 in.	Included	0.5	6.0	150	390	
Horizontal - Rectangular	3¼ in. x 10 in.	Included	0.6	5.5	150	400	
Round - Vertical	7 in.	Sold Separately	0.4	5.5	150	390	

FEATURES	
Control type	2-speed Rocker
Delay off	no
Filter Clean Reminder	no
Heat Sentry™	no
ADA Capable	yes
Lighting	2-level 50 W Halogen (included)
Grease Filters	Hybrid/Baffle (Qty. 2)
Installation Hardware	EZ1 brackets
ENERGY STAR®	no
Recirculation	Non-ducted filters sold separately
AC INDIT	

120V, 60 Hz - 2.2 AMPS

,				
OPTIONAL ACCESSORIES				
7-in. Round Damper	BP87Q			
7-in. Round Adapter Plate	SR680508			
ADA wiring kit	HAWRK3			
Make-up Air Dampers	MD6TU, MD8TU and MD10TU			

MOUNTING HEIGHT


18-in. to 30-in. from cooktop to bottom of hood

LIMITED WARRANTY

1-year

FOR INDOOR USE ONLY Vertical High Speed, 0.8 7-in. round © 0.7 Vertical High Speed, with 3% in. x 10 in. damper 0.6 Horizontal High Speed, with 3¼ in. x 10 in. damper 0.5 0.4 0.3 0.2 0.1 150 350 450 250 400 Airflow (cfm)









HVI-2100 CERTIFIED RATINGS comply with new testing technologies and procedures prescribed by the Home Ventilating Institute, for offthe-shelf products, as they are available to consumers. Product performance is rated at 0.1 in. static pressure, based on tests conducted in AMCA's state-of-the-art test laboratory. Sones are a measure of humanly-perceived loudness, based on laboratory measurements.