SPECIFICATION SHEET



The slim and refined lines of Sahale bring a refreshing change to today's kitchens. Bright Halogen lighting complements your cooking experience and two fan speeds make cooking more enjoyable.

SIZE	WHITE	BLACK	STAINLESS	GREASE FILTERS (replacement)	NON-DUCTED FILTERS
30 in.	BKSH130WW	BKSH130BL	BKSH130SS	HPFAMM30 (Type C1/C2)	HPF30 (Type Xc)

PERFORMANCE								
Donat Orientation	Size	Damper	Sones		CFM			
Duct Orientation			Normal	High	Normal	High		
Vertical - Rectangular	3¼ in. x 10 in.	Included	1.5	5.0	140	230		
Horizontal - Rectangular	3¼ in. x 10 in.	Included	1.5	5.0	110	210		
Round - Vertical	7 in.	Sold Separately	1.5	5.0	150	250		

FEATURES				
Control type	2-speed Deluxe Rocker			
Delay off	no			
Filter Clean Reminder	no			
Heat Sentry™	no			
ADA Capable	yes			
Lighting	2-level 50W Halogen (included)			
Grease Filters	Micro Mesh (Qty. 2)			
Installation Hardware	EZ1 brackets			
ENERGY STAR®	no			
Recirculation	Non-ducted filters sold separately			
AC INPUT				
120 V 60 Hz - 1 4 AMPS				

| 120 V, 60 Hz - 1.4 AMPS

OPTIONAL ACCESSORIES

BP87Q 7-in. Round Damper Make-up Air Dampers MD6TU, MD8TU and MD10TU


MOUNTING HEIGHT

18 in. to 24 in. from cooktop to bottom of hood


LIMITED WARRANTY

1-year

FOR INDOOR USE ONLY









Broan-NuTone LLC

Venmar Ventilation ULC



HVI-2100 CERTIFIED RATINGS comply with new testing technologies and procedures prescribed by the Home Ventilating Institute, for off-the-shelf products, as they are available to consumers. Product performance is rated at 0.1 in. static pressure, based on tests conducted in AMCA's state-of-the-art test laboratory. Sones are a measure of humanly-perceived loudness, based on laboratory r

99045753C