


MODEL 673 VERTICAL DISCHARGE CEILING FAN



Economy and performance that fits the bill in vertically ducted fans.

FEATURES

GRILLE:

- Matte white polymeric
- Spin-on mounting

MOTOR:

- Plug-in, thermally protected, permanently lubricated
- Durable polymeric fan blade

HOUSING:

- Galvanized steel housing
- 23 gage mounting brackets with keyhole slots
- Built-in damper helps eliminate backdrafts

SPECIFICATIONS

VOLTS	AMPS	RPM	SONES	CFM	DUCT
120	1.0	2600	4.5	60	6" Round



HVI-2100 CERTIFIED RATINGS comply with new testing technologies and procedures prescribed by the Home Ventilating Institute, for off-the-shelf products, as they are available to consumers. Product performance is rated at .03 in. static pressure, based on tests conducted in a state-of-the-art test laboratory. Sones are a measure of humanly-perceived loudness, based on laboratory measurements.



TYPICAL SPECIFICATION



Ventilator shall be Broan Model 673.

Unit shall have galvanized steel housing. Mounting brackets with keyhole slots. Backdraft damper to be built-in.

Motor assembly shall be permanently lubricated and removable from housing. RPM not to exceed 2600.

Air delivery shall be no less than 60 CFM and sound levels no greater than 4.5 Sones. All air and sound ratings shall be certified by HVI.

Unit shall be U.L. Listed.



Broan-NuTone LLC, Hartford, WI 53027 www.broan-nutone.com 800-558-1711

REFERENCE	QTY.	REMARKS	Project
			Location
			Architect
			Engineer
			Contractor
			Submitted by Date