



STAIN-FREE PLUMBER'S PUTTY TECHNICAL SPECIFICATION

Job Name _____	Item # _____
Location _____	
Engineer _____	Contractor _____
PO # _____	Tag _____
Representative _____	

DESCRIPTION

- Oatey Stain-Free Plumber's Putty is a stain-free sealant for setting most types of plumbing fixtures, with just the right amount of tack to adhere and shape.
- Oatey Stain-Free Plumber's Putty remains flexible, so it is easy to work with, molds easily, and cleans up easily.
- Oatey Stain-Free Plumber's Putty provides a waterproof seal between two rigid surfaces.

APPLICATION / USES

- Oatey Stain-Free Plumber's Putty is an oil-free, professional grade, non-staining plumber's putty that is formulated for use on natural surface materials found in sinks, countertops, strainers and shower bases such as granite, marble, quartz/sandstone, and Corian® **(NOT FOR USE ON ABS)**.
- Oatey's Stain-Free Plumber's Putty can be used for setting frames, faucets and basket strainers.

Consult Oatey Technical Service department for applications not specified above.

PHYSICAL PROPERTIES / INGREDIENTS

NON-HAZARDOUS INGREDIENTS	
NJ TSNR: 80100453-5020	
PHYSICAL/CHEMICAL PROPERTIES	
Specific Gravity	1.75
Solubility in Water	Insoluble
Flash Point	450°F
Drying Time	No wait required
Shelf Life	1 year from manufacture date
Appearance	Off-white putty
Odor	Mild, sweet

PRODUCT NUMBER	DESCRIPTION	PACK	CARTON WEIGHT (LBS.)
31177	9 oz. net wt. (plastic cup)	18	11



PRECAUTIONS

Read all cautions and directions carefully before using this product. **NOT FOR USE ON ABS.** DO NOT MIX OATEY STAIN-FREE PLUMBER'S PUTTY WITH NORMAL GRADES OF PLUMBER'S PUTTY AS STAINING MAY OCCUR. For out of the ordinary materials not normally used as countertops or plumbing fixtures, test in an inconspicuous area first before using, or consult the manufacturer for recommended sealants. Keep container closed when not in use. DO NOT REUSE EMPTY CONTAINER. KEEP OUT OF REACH OF CHILDREN AND PETS.

Refer to material safety data sheet for more information.
For emergency first aid help, call 1-877-740-5015.

DIRECTIONS

All surfaces must be dry and free from hardened putty, dirt, wax, oil and grease. Remove debris by wiping with cloth, scraper or wire brush as needed and dry surface. Knead putty in hands and form a long cord-like shape. Lay out the cord-like putty on the surface to be sealed, overlapping the ends. Place the fixture over the bead, attach and secure the fixture in place. Excess Plumber's Putty should squeeze out from around the fixture ensuring sufficient putty has been applied and a continuous seal has been made. Remove excess with a putty knife.