



4700 W. 160th St.  
Cleveland, OH 44135  
PH:800-321-9532  
FX:800-321-9535  
www.oatey.com

**TECHNICAL SPECIFICATION**

**METAL STUD  
INSULATING PIPE CLAMPS**



**TECHNICAL SPECIFICATION:** Oatey Metal Stud Insulating Pipe Clamps can be installed to isolate piping away from the stud and reduce water line noise and vibration in metal stud installations. Metal Stud Insulating Pipe Clamps snap into 1-3/8" punched hole and can be used on 18 Gauge or lighter weight metal studs. Metal Stud Insulating Pipe Clamps can be used on hydronic heating systems.



**APPROVALS AND LISTINGS**



IAPMO Listed

**PHYSICAL/CHEMICAL PROPERTIES**

Material Polypropylene  
Color Gray

**DIRECTIONS FOR USE**

Punch 1-3/8" hole in metal stud. Snap clamp into hole. Clamp is offset to allow for adjustment of centers from stud to stud. 1/2" clamp allows for 1/4" and 3/8" tubing installation through secondary holes in clamp. Check with local codes to ensure proper spacing requirements for piping support.

**PRECAUTIONS**

Read cautions and directions on packaging carefully before using this product. KEEP OUT OF REACH OF CHILDREN.

**COMMON APPLICATIONS**

Oatey Metal Stud Insulating Pipe Clamps can be installed to isolate piping away from the stud and reduce water line noise and vibration in metal stud installations. *U.S. Patent #6,598,835.*

Consult Oatey Technical Department for applications not specifically referenced above.

PRODUCT NUMBER	DESCRIPTION	PACK	CARTON WEIGHT
33856	1/2" Metal Stud Clamp (50 in polybag)	250	2.5 lbs.
33857	3/4" Metal Stud Clamp (50 in polybag)	250	2.5 lbs.
33858	1" Metal Clamp (25 in polybag)	250	2.5 lbs.