

MODA™ FIRE-RATED DRAIN BOX TECHNICAL SPECIFICATION

SPECIFICATIONS

Oatey MODA™ fire-rated drain box shall be used in residential or commercial applications requiring a waste drain recessed in the wall. The MODA™ fire-rated drain box assembly contains a box with interlocking flanges on each side. Box shall be manufactured of PVC, allowing solvent weld joints to be prepared in accordance with ASTM D2855 for PVC drainage systems (without the use of specialty cements). The wing flanges in conjunction with the metal bracket allow for direct to stud installation. L-shape brackets are included for support based on wall rating (see instruction sheet). The assembly shall include a removable quarter-turn knock out plug for DWV testing, and shall include an emergency drain port for added protection from valve leaks.

APPROVALS & LISTINGS

Boxes	IAPMO-Listed, PS-54			
Listed with Massachusetts Board of Plumbing Listed by Warnock Hersey to meet: ASTM E814, UL 1479				
2-Hour Design	F-Rating: 2 Hour, T-Rating: 1-1/4 Hour			
1-Hour Design	F-Rating: 1 Hour , T-Rating: 3/4 Hour			
Listed by Warnock Hersey to meet: CAN/ULC S115				
2-Hour Design	FH Rating: 2 Hour, FTH Rating: 1-1/4 Hour			
1-Hour Design	FH Rating: 1 Hour, FTH Rating: 3/4 Hour			





FEATURES & MATERIALS

Outlet Box & Brackets	PVC
Metal Bracket and L-shape Brackets	16 Gauge Galvanized Steel

DIMENSIONS

[A]:	Box Width	7.98"	[E]:	Bracket Length	8.00"
[B]:	Box Depth	3.63"	[F]:	Faceplate Width	6.00"
[C]:	Box Height	4.85"	[G]:	Faceplate Height	6.45"
[D]:	Bracket Width	4.00"	[H]:	Faceplate Depth	1.25"

PRODUCT SELECTOR

NO HAMMER ARRESTORS			
\checkmark	Product Number	Description	
	37450	MODA FR, Plain Drain Box	

All products sold in single case packs



Accessory Components Included:







Test Plug



Sticker Cover (1) (For Debris Protection)



Intumescent Pad (Pre-installed)



Metal Brackets (1)



L-shape Brackets (2)





