



OLYMPIA FAUCETS, INC.
3325 S. Garfield Ave.
Commerce, CA 90040
(888) 772-7701
www.olympiafaucets.com

INSTALLATION

Tools:



Adjustable Wrench



Plumbers Putty



Teflon Tape



Rags

Model Number: OP-630002, OP-630004

Warnings and Notes:

Check with local plumbing code requirements before installation.

This product should be installed by a local listed plumber.


Do not use plumbers putty on threads.

Installation Steps:


Pop-Up Drain Assembly

“DO NOT USE THREAD SEALANTS, TEFLON TAPE ONLY”


“NO USE SELLADORES DE ROSCA, UTILIZAR SOLO CINTA DE TEFLON”




- (1) a. For brass pop-up: Remove flange from drain body.
b. For 50/50 type pop-up: Remove rubber gasket, flat washer, and lock nut from metal drain body.




- (2) a. For brass pop-up: Place a ring of plumbers putty on the bottom of the flange and apply Teflon tape on threaded tailpiece. Thread tailpiece to drain body. Insert flange through drain hole and attach drain body to flange from underneath the sink.
b. For 50/50 type pop-up: Place a ring of plumbers putty on the bottom of the flange. Insert drain body through drain hole. Thread rubber gasket, flat washer, and lock nut onto drain body. Apply Teflon tape only on the threaded area and attach tailpiece to drain body. **Please Note: Use Teflon tape only on all thread connection areas. Using pipe thread sealant might weaken material structure and cause leaks.**




- (3) Insert pop-up flange through drain hole and attach flange to the pop-up drain body. Apply Teflon tape on the threaded end of the tail piece and attach tail piece to the pop-up drain body. Ensure the pivot rod hole of the pop-up drain body faces towards the back of the sink. Tighten the locknut with the help of a wrench to secure the pop-up drain body.




- (4) Remove the excess plumbers putty. Connect the trap (check manufacturer's instructions for installation).



- (5) Remove pivot rod nut from pop-up body, ensure the washers is in place, insert pivot rod, tighten pivot rod nut back to pop-up body.



- (6) Push pivot rod down, insert drain plug carefully. Test to ensure drain plug works properly.



- (7) Connect lift rod strap to pivot rod by using clip. Tighten the thumbscrew to connect lift rod strap to pop-up lift rod.



For more care information or trouble shooting inquiries about your Olympia product, Please call:

OLYMPIA FAUCETS, INC. (888) 772-7701

Monday-Friday 8 AM to 8 PM EST (5 AM to 5 PM PST)

www.olympiafaucets.com