INSTALLATION



OLYMPIA FAUCETS, INC.

3325 S. Garfield Ave. Commerce, CA 90040 (888) 772-7701 www.olympiafaucets.com

Tools:











Adjustable Teflon Tape Hacksaw& Pipe Cutter Wrench

Torch

Propane Lead-Free PEX Crimp Solder Tool

Model Number: V-2500B

Warnings and Notes:


Check with local plumbing code requirements before installation.

This product should be installed by a local listed plumber.


Do not use plumbers putty on threads.

Installation Steps:


Single Handle Tub/Shower Pressure Balancing Valve With Built-in 2 Way Diverter









(2) Installation Distance Without Bracket.




(3) For Tub Spout Use 1/2" copper or IPS Pipe Only For Shower Only Use Provided 1/2" Cap to cap tub outlet.




(4) Install Valve with 2 Wood screws provided.




(5) For CXC Installation :- Remove Sleeve Nut, Cartridge and Inlet Stop Assemblies before soldering.




(6) Connect valve body to water inlets using the proper fittings (Copper, IPS, PEX-Crimp, PEX-Cold Expansion, CPVC). Note:- For PEX, be sure to use the right fitting for crimping and the right fitting for Cold Expansion.




(7) Ensure Valve is leveled. To check vertical leveling remove level and put in the front hole in mud guard.




(8) For CXC Installation :- Assemble Cartridge, Sleeve Nut and Inlet Stop Assemblies after installation was completed.




(9) Turn on water supplies then turn the cartridge to the left and to the right to test the valve function properly.



(10) **For Thin Wall Installation:-** Use Provided template for thin wall installation.



(11) Remove Mud guard screws.



(12) Use Mud guard screws to secure valve to thin wall.

Exploded Drawing:

	ITEM#	DESCRIPTION
Α	OP-440059	Mud Guard
В	OP-440053	Sleeve Nut
С	X-3400008	Pressure Balancing Two Way Diverter Cartridge
D	OP-440007	Inlet Stop Assembly
Е	OP-440023	Protective Cap
F	OP-540003	Mounting Bracket With Screws
G	X-4900025	Cap and Washe
1	OP-440063	Mud Guard Screw
2	X-4900055	Mounting Bracket Screws

