

Victorian FS3 Series



FEATURES & OPTIONS

Door Prep.

Cross Bore: 2-1/8" , Edge: 1"
Center to Center: 5-1/2"

Interior Trim

FT3-Saturn knob interior trim
(other options available)

Latch Backset

Deadbolt: 2-3/8" deadbolt standard
Handle: 2-3/8" plainlatch standard
(other options available)

Faceplate

1" x 2-1/4" round corner standard
(other options available)

Bolt

Deadbolt: 1" throw
Lever: 1/2" throw

Door Thickness

Fit 1-3/8" to 1-3/4" standard
(extension kit available for 1-3/4" to 2-1/4" door)

Cylinder

5-pin KW keyway solid brass cylinder standard
5-pin SC "C" keyway available

Strike Plate

Deadbolt: 2-1/4" x 1-3/4" full lip round corner standard
Handle: 2-1/4" x 1-3/4" full lip round corner standard
(other options available)

Handing

Specify handing when order lever interior trim

ANSI/BHMA

A 156.2 Grade 3

FINISHES

(other finishes available upon request with lead-time)

- US3 – 605 – Polished Brass
- US5 – 609 – Antique Brass
- US15 – 619 – Satin Nickel

WARRANTY

- Lifetime mechanical warranty
- Five years finish warranty

FUNCTIONS

Single Cylinder

Deadbolt operated by key outside and turn-piece inside. Latchbolt operated by thumb-piece outside and knob or lever inside.

Double Cylinder

Deadbolt operated by key on both sides. Latchbolt operated by thumb-piece outside and knob or lever inside.

Dummy

Handle and knob or lever act as pull only. No operation.

