



LAVATORY FAUCET

- Single Handle Deck Mount
- 1 or 3 Hole Sink Applications

STANDARD SPECIFICATIONS:

- Maximum flow rate 1.2 gpm @ 60 PSI, 4.5L/min @ 414Kpa.
- Solid brass body.
- Single handle lavatory deck faucets for exposed mounting on 1 or 3 hole sinks.
- 3 15/16" (100 mm) long fixed spout.
- Centermount or 4" (102 mm) centers with optional 5 15/16" (150mm) escutcheon.
- Polymer braided flexible supply hose with 3/8" compression connection.
- Lever handle. Control mechanism is replaceable cartridge with ceramic plates.
- Models have 50 / 50 pop-up drain assembly.

WARRANTY

- Lifetime limited warranty on parts (other than electronic parts and batteries) and finishes; or, for commercial users, for 5 years from the date of purchase.
- 5 year limited warranty on electronic parts (other than batteries); or for commercial users, for 1 year from the date of purchase. No warranty is provided on batteries.



COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1
- ASME A112.18.2 / CSA B125.2
- Indicates compliance to ICC / ANSI A117.1
- EPA WaterSense®
- Verified compliant with 0.25% weighted average Pb content regulations