

K240

PRODUCT FEATURES


- Style: Traditional
- Collection: Versailles
- Temperature Controlled By Handles
- Lever Handles
- Split Finish: Green Onyx

TECHNICAL DETAILS

ADA Compliance: Yes
 Deck Thickness Maximum: 1"
 Deck Thickness Minimum: 1/8"
 Drain Assembly Material: Brass
 Drain Style: Lift Pop-up
 Fitting Hole Diameter: 1 1/8"
 Number of Holes: Three Hole
 Number of Handles: Two
 Handle Spread Maximum: 12"
 Handle Spread Minimum: 8"
 Handle Turn Angle: Quarter Turn
 Spout Reach: 5 3/16"
 Spout Height: 3 5/8"
 Inlet Connection Type: Male 1/2" NPSM
 Installation Type: Deck Mounted
 Primary Material: Brass
 Valve Material: Ceramic
 Flow Restriction: 1.2 gpm
 Water Pressure Maximum: 85 PSI
 Water Pressure Minimum: 20 PSI
 Water Pressure Recommended: 60 PSI

- Available Split Finish Options:
Montaione Brown Onyx / Blue Sodalite / Pink Onyx / Fienze Black Onyx

PRODUCT DIMENSIONS


www.phylrich.com

1261 Logan Avenue, Costa Mesa, California 92626.
 Phone: 714.361.4800 Fax: 714.617.3120



CODES & STANDARDS

ASME A112.181/ CSA B1251, ASME 112.18.2/ CSA B125.2, ANSI NSF, CEC

WARRANTY

Mechanical Warranty: 10 Years from date of purchase.
 Finish Warranty: See catalog for further information.

Rev-