

## Air Pro Builder Fan

 Ceiling downrod Mounted • Dry Location Listed **PROGRESS LED**

### Description:

Air Pro 52 in. Matte Black 5-Blade AC Motor Transitional Ceiling Fan with Light

### Specifications:

- Frosted Polypropylene Shatter Resistant Diffuser
- Canopy covers a standard 4" recessed outlet box: 5 in W., 2.25 in ht., 5 in depth
- Hdwr. Included
- 80 in of wire supplied

### Performance:

|                 |                                    |
|-----------------|------------------------------------|
| Number of Lamps | 2                                  |
| Input Power     | 8.5 W                              |
| Input Frequency | 60 Hz                              |
| CCT             | 3000 K                             |
| CRI             | 80 CRI                             |
| Life (hours)    | 15000 (L70/TM-21)                  |
| EMI/RFI         | FCC Title 47, Part 15, Class B     |
| Warranty        | 30-year Limited Warranty           |
| Labels          | UL Dry Location Listed<br>AC motor |

# P250082-31M-WB



### Dimensions:

Length: 52 in  
 Diameter: 52 in  
 Height: 16-11/16 in

Frosted Polypropylene Shatter Resistant Diffuser

## ENERGYGUIDE

Estimated  
Yearly Energy Cost

# \$10

\$3

↓

\$34

Cost Range of Similar Models (19" – 84")

- Based on 12 cents per kWh and 6.4 hours use per day
- Your cost depends on rates and use
- Energy Use: 36 Watts

Airflow

# 3,293

Cubic Feet Per Minute

- The higher the airflow, the more air the fan will move
- Airflow Efficiency: 92 Cubic Feet Per Minute Per Watt

All estimates based on typical use, excluding lights ftc.gov/energy