

# OLSON

Ceiling mounted • Dry location listed

## Description:

The 52" Olson five-blade ceiling fan features a generously sized etched watermark glass shade and sweeping blades highlighted with metal accents. Two 10W LED lamps are JA8 compliant, offering both form and function with energy and cost-savings benefits. Olson features a dual mount system and a three-speed pull chain fan switch, as well as an on/off pull chain switch to operate the light.

## Specifications:

- Brushed Nickel (-09) (plated)
- Steel construction
- White Opal Glass Bowl
- 52" Olson Collection ceiling fan features five generously sized sweeping reversible blades
- Reversible Medium Cherry and Classic Walnut blades
- Timeless Brushed Nickel finish
- Features a dual mount system and a three-speed pull chain fan switch, as well as an on/off pull chain switch to operate the light
- Pull chain is chrome
- Add an accessory wall or remote control for added convenience
- Indoor ceiling fan ideal for use in great rooms, living rooms, bedrooms and bonus rooms
- Ceiling fan adds form and function – by providing increased air circulation in rooms
- Features Transitional design styling
- Powerful and reversible 3-speed motor with triple-capacitor control
- As a general rule of thumb, lighting experts suggest this fan is ideal in a room size that ranges from 226- to 400-square feet
- Light kit features white opal glass
- Two 10W LED lamps are JA8 compliant, offering both form and function with energy and cost-savings benefits
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" octagonal recessed outlet box
- Mounting Yes for outlet box included
- 80" of wire supplied
- Classic Walnut/Medium Cherry reversible blades, plywood construction
- Chrome pull chain with Brushed Nickel fob
- 13.5 blade pitch
- Triple capacitor speed control, manual reverse control Speed, Manual Reverse
- Airflow: 5023 CFM\*
- Energy consumption: 69 watts (excluding lights)\*
- Airflow efficiency: 72 cfm/watt\*
- \* Fan on a downrod

## Performance:

Number of Modules	2
Input Power	10w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW	1600/80 (LM-79) per module
CCT	3000 K
CRI	90 CRI
Life (hours)	25,000 (L70/TM-21)
Warranty	Limited Lifetime
Labels	cULus Dry location listed

## P2598-09

## Images:



## Dimensions:

Diameter: 52"  
Height: 21-3/8"

Glass  
Width: 11"  
Height: 5-1/8"

**P2598-09****Dimming Notes:**

---

P2598 is designed to be compatible with many Triac/Forward Phase or ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

**Dimming Controls**

---

Leviton - 6672

Leviton - IPI06-1LZ

Lutron - AYCL-153PH

Lutron - SCL-153PH-WH

Lutron - TGCL-153PH-WH

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.