

LagosSeries

ADJUSTABLE LINEAR DRAIN

3" High Flow

Adjustable Base | Traditional Waterproofing:

- Stainless Steel Gauges: Grates: 16 gauges.
- PVC Base: 3 mm
- Grate can be removed completely for cleaning.
- Adjustable is intended for use with traditional waterproofing methods.



Kit Includes:

- Base
- Outlet**
- End Cap
- Grate*
- Trims
- Lifting Key
- Leveling Feet
- Threaded Nipple
- Stainless Steel Cutting Blade



Specifications

Base

L: 32" / 44" / 56" / 68" / 92"

3.43"

1.44"

Outlet**

4"

End Cap

Grate (Tile Insert)*

36" / 48" / 60" / 72" / 96"

* 72" and 96" kits in black, gold and bronze have two grates.

Joiner

3.44"

A Joiner is needed to connect kits to build the desired length. It is sold separately. It is not part of the kit.

SKU: 88.JOINER

Corner

4" x 4"

A corner is needed when connecting two channels at a 90-degree angle. Corner is an accessory, it is sold separately. It is not part of the kit.

SKU: 88.601.COR

3.15"

2.80"

0.56"

0.82"

Note: The Tile-In grate accepts flooring material up to 3/8" thickness.

Complete Kits

MIST (TILE-IN)			
 Bronze	36"	88.610.36HF BZ	
	48"	88.610.48HF BZ	
	60"	88.610.60HF BZ	
	72"	88.610.72HF BZ	
	96"	88.610.96HF BZ	
 Satin	36"	88.630.36HF ST	
	48"	88.630.48HF ST	
	60"	88.630.60HF ST	
	72"	88.630.72HF ST	
	96"	88.630.96HF ST	
 Polished	36"	88.630.36HF PS	
	48"	88.630.48HF PS	
	60"	88.630.60HF PS	
	72"	88.630.72HF PS	
	96"	88.630.96HF PS	
 Black	36"	88.630.36HF BK	
	48"	88.630.48HF BK	
	60"	88.630.60HF BK	
	72"	88.630.72HF BK	
	96"	88.630.96HF BK	
 Gold	36"	88.630.36HF GD	
	48"	88.630.48HF GD	
	60"	88.630.60HF GD	
	72"	88.630.72HF GD	
	96"	88.630.96HF GD	

Note: Installer must verify all rough-in dimensions prior to installation and consult local and national codes. Conformity and compliance to local and national codes are the responsibility of the installer. Dimensions are subject to manufacturers tolerance and change without notice. We can assume no responsibility for use of superseded or voided data. [Contact us if you have any question at: info@qm-us.com](mailto:info@qm-us.com)