

Project: Type: Prepared By: Date:



## **Features and Benefits**

Energy efficient replacement for incandescent and halogen Small diameter reflectors

Constructed from durable materials which lowers risk of breakage

Rated for use in enclosed and open fixtures in dry or damp locations

Single optic and full face lens for precise beam angle control

 $Longer\,life span\,compared\,to\,legacy\,equivalents\,minimizes\,replacement\,and\,maintenance\,costs$ 

**ENERGY STAR Compliant, UL Listed** 

## **Technical Specifications**

Performance

**Product Type:** 

Small-Reflector

Input Wattage:

4.5W

Lumens (Nominal):

350lm

Efficacy:

77 lm/W

L70 Lifespan:

25,000-Hour LED lifespan based on IES LM-70 results

Wattage Equivalency:

50

**LED Characteristics** 

Color Accuracy (CRI):

80

**Color Temperature:** 

2700K

Electrical

**Power Factor:** 

>0.7

Dimmable:

Yes, down to 10%

Input Voltage:

120V

Operating Frequency:

60 Hz

**Operating Temperature:** 

-20°C-45°C

Construction

**Bulb Shape:** 

PAR16

**Enclosure Material:** 

Plastic

**Housing Finish:** 

White

Base Type:

GU10



**Technical Specifications (continued)** 

Optical

**UL Listed:** 

Yes

Compliance

Complies with Part 15 of the FCC Rules

Beam Angle: 35°

Other

**Environment/Fixture Rating:** 

Mercury and UV free. RoHS-compliant components.

**Model Number:** 

FCC:

Technology EQ:

Damp / Enclosed

Rohs: Halogen

R10059(GU10-4.5-827-35D-DIM)

Warranty (Years):

3 years

## **Minimum Compartment Size**

Length x Width x Height [in]	Lamp Quantity
10.43 x 4.33 x 2.76	1

## **Case and Pallet Dimensions**

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	10	0	0	0
PALLET	3120	0	0	0

