

Project: _____ Type: _____ Prepared By: _____ Date: _____



Features and Benefits

- Omni directional light distribution
- Suitable for horizontal or vertical installations
- Replaces 26W/32W G24d & G24q
- Plug and Play on existing Magnetic CFL ballasts or can be wired directly to line voltage without need for an external driver or ballast
- Compatible with G24d / GX24d & G24q / GX24q installations
- 50,000 hour Lifespan
- Environmentally friendly, no mercury used
- UL Listed, UL Classified
- Rated for use in enclosed and open fixtures in dry or damp locations
- Non-Dimmable
- 5 Year No Compromise Warranty

Technical Specifications		
Performance	LED Characteristics	Operating Frequency:
Product Type: Compact	Color Accuracy (CRI): 80	50/60Hz
Input Wattage: 7W	Color Temperature: 3500K	Operating Temperature: -20°C - 45°C (-4°F - 113°F)
Lumens (Nominal): 880lm	Electrical	Construction
Efficacy: 126 lm/W	THD: 20%	Bulb Shape: PLC-O
L70 Lifespan: 50,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations	Power Factor: >0.9	Enclosure Material: Polycarbonate
Wattage Equivalency: 13W/18W G24d & G24q	Dimmable: Non-Dim	Housing Finish: White
	Input Voltage: 120-277 Type B (Type A dependent on ballast)	

Technical Specifications (continued)

Construction

Lens Finish:

Frosted

Base Type:

2-Pin G24d

Optical

Beam Angle:

360°

Installation

Installation Method:

UL Type A with Magnetic Ballasts & UL Type B (Dual Mode)

Burning Position:

Universal

Other

Technology EQ:

CFL

Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Compliance

Safety Listing:

UL Listed, UL Classified

Environment/Fixture Rating:

Damp / Enclosed

RoHS:

Mercury and UV free. RoHS-compliant components.

FCC:

Complies with Part 15 of the FCC Rules

Model Number:

T10188(PLC-7-O-835-HYB)


Minimum Compartment Size

Length x Width x Height [in]	Lamp Quantity
6.1 x 6.2 x 4.8	1

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	12	0	0	0
PALLET	808	0	0	0

Dimension



Light Distribution

