Construction

Automotive Industry



PRODUCT SUBMITTAL 625

Product: Variable Speed Mixing Control

Date: 05 April 2013 (supersedes 07 August 2009)



Article No.	Description
236327-001	Variable Speed Mixing Control (361)

TECHNICAL DESCRIPTION

Power supply:	120 V +/- 10%, 50/60 Hz, 1300 VA
Relays:	240 VAC, 10A, 1/3 hp
Demands:	20 to 260 VAC, 2 VA
Enclosure:	Black PVC plastic
Dimensions:	6 5/8 H x 7 9/16 W x 2 13/16 in. D (17.0 x 19.3 x 7.2 cm)

FUNCTIONAL DESCRIPTION

The variable speed mixing control is an outdoor reset control designed to control the mixed supply water temperature to a radiant system. The variable speed mixing control operates a variable speed injection pump to regulate the supply water temperature while still protecting the boiler against flue gas condensation. This control also provides for boiler operation, primary pump operation and secondary pump operation.

For updates to this publication, visit na.rehau.com/resourcecenter

The information contained herein is believed to be reliable, but no representations, guarantees or warranties of any kind are made as to its accuracy, suitability for particular applications or the results to be obtained therefrom. Before using, the user will determine suitability of the information for user's intended use and shall assume all risk and liability in connection therewith

www.rehau.com PS625, 05-Apr-13, Page 1 of 1