Construction

Automotive Industry



PRODUCT SUBMITTAL 284

Product: PRO-BALANCE® Isolation Valve

Date: 3 July 2012



Article No.	Description
250216-	1 in. NPT x 1 in. BSPP Isolation Valve Set, One Red and One Blue Handle
244777-	1 in. NPT x 1 in. BSPP Isolation Valve, Red Handle
281931-001	1 1/4 in. NPT x 1 1/4 in. BSPP Isolation Valve Set, One Red and One Blue Handle

TECHNICAL DESCRIPTION

Material	Brass valve with fiber gasket
----------	-------------------------------

FUNCTIONAL DESCRIPTION

PRO-BALANCE isolation valves can be used to shut off flow of the system fluid. These valves connect directly to the PRO-BALANCE brass manifold supply/return sides with a BSP threaded connection that uses the included fiber gasket. These valves have integrated thermometer housings on each side of the valve housing. Mini thermometers (Art. 250218) can be set into these housings to give accurate readings of temperatures on both supply and return sides of any PRO-BALANCE brass manifold. Mini thermometers are sold separately.

For updates to this publication, visit na.rehau.com/resourcecenter

The information contained herein is believed to be reliable, but no representations, guarantees or warranties of any kind are made as to its accuracy, suitability for particular applications or the results to be obtained therefrom.

© 2012 REHAU

www.rehau.com PS284, 03-Jul-12, Page 1 of 1