

# PRODUCT SUBMITTAL 532

**Product:** Heat Exchanger  
**Date:** 01 January 2017 (supersedes 03 June 2009)



Article No.	Description
266477	Heat Exchanger, 3/4" MPT Connections (100,000 Btu load)
266487	Heat Exchanger, 3/4" MPT Connections (150,000 Btu load)

### *TECHNICAL DESCRIPTION*

Material	Stainless Steel
----------	-----------------

### *FUNCTIONAL DESCRIPTION*

Compact, stainless steel heat exchanger for use in radiant heating and snow and ice melting projects. Applications include: radiant heating systems using a domestic hot water tank as the heat source to separate heating water from drinking water (check local codes) and SIM systems using concentration of glycol (antifreeze) different than the rest of the hydronic system. CSA and UL approved. Can provide more than 100,000 Btu/hr, depending on temperatures and flow rates, has 1/4 - 20 studs for mounting.

#### Specifications:

- Maximum working pressure: 450 psi (31 bar)
- Maximum operating temperature: 350°F (177°C)

For updates to this publication, visit [na.rehau.com/resourcecenter](http://na.rehau.com/resourcecenter)

The information contained herein is believed to be reliable, but no representations, guarantees or warranties of any kind are made as to its accuracy, suitability for particular applications or the results to be obtained therefrom. Before using, the user will determine suitability of the information for user's intended use and shall assume all risk and liability in connection therewith.

© 2017 REHAU