

PRODUCT SUBMITTAL PS1300

Product: EVERLOC+™ LF Brass Swivel Adapters
Date: 01 August 2017 (supersedes 01 January 2017)



Article No.	Nominal Size (in.)
418463-001	1/2 x 1/2 NPS Female Swivel Adapter
418464-001	3/4 x 3/4 NPS Female Swivel Adapter

TECHNICAL DESCRIPTION

Specification	ASTM F877 / CSA B137.5
Material	ECO BRASS® (C69300 or CW724R), EPDM
Certifications	cNSFus-pw

FUNCTIONAL DESCRIPTION

EVERLOC+ compression-sleeve fittings and sleeves are designed specifically for use with REHAU PEXa pipe. The maximum temperature and pressure ratings of the EVERLOC+ compression-sleeve fitting system is in accordance with ASTM F877 and CSA B137.5 for SDR9 PEX, see REHAU pipe product submittals for ratings. Installation is performed with EVERLOC+ compression-sleeve tools. Follow all published REHAU *Technical Guidelines*. All EVERLOC+ fittings and sleeves comply with the lead-free (LF) requirements of the U.S. Safe Drinking Water Act.

Swivel adapters connect REHAU PEXa pipe to connections with male threaded ends. The captured swivel nut turns freely to make convenient connections. This allows the EVERLOC+ connection to be made in an open space before attaching the fitting to a mating part in a more confined location. Fitting is supplied with a flat EPDM gasket for the internal seal. Swivel adapters use parallel threads, not tapered threads. Do not use pipe dope or thread sealant - the flat gasket makes the seal. Swivel adapters cannot be walled in and must be accessible for inspections.

For updates to this publication, visit na.rehau.com/resourcecenter

The information contained herein is believed to be reliable, but no representations, guarantees or warranties of any kind are made as to its accuracy, suitability for particular applications or the results to be obtained therefrom. Before using, the user will determine suitability of the information for user's intended use and shall assume all risk and liability in connection therewith.

© 2017 REHAU