

Project Name

Location

Prepared By



SATCO S11545

14W/LED/CFL/3CCT/BP/GX32D-2

Notes

(www) 10-31-2023 23:30:23

General

Status	Active
Watts	14W
Fluorescent Equivalent	22W
Volts	120V-277V
Ballast Type	Type B
Shape	PL
Base	GX32d-2
ANSI Base	GX32d-2
Finish	Frost
CCT (Kelvin)	2700K/4000K/5000K
Temperature	Warm White to Natural Light
CRI	80+
Lumens	1400L
Beam Spread	320
Dimmable	Non-Dimmable
Hours Rated	15000
Product Category	PL
Operating Position	Universal
Technology	LED

Electrical

Ballasting Requirements	Ballast Bypass
Operating Frequency	60Hz
Power Factor	>0.9
THD	<20%
Operating Temperature	-20C (-4F) to +40C (+104F)

Physical

MOL	6.3
MOD	1.93
Housing Color	White
Weight (lb.)	0.3

Additional Information

Rated For Enclosed Fixture	No
Warranty	2-Years

Compliance

Safety Listing	cETLus - Classified
Location Rating	Damp
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp