

Project Name

Location

Prepared By



Notes

**General**

Status	Active
Watts	11.5
Fluorescent Equivalent	32
Volts	120V-277V
Ballast Type	Type B
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48
Finish	Frosted
CCT (Kelvin)	3500
Temperature	Neutral White
CRI	80
Lumens	1650
Beam Spread	180
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Linear
Technology	LED

**Electrical**

Ballasting Requirements	Ballast Bypass; Direct wire 120-277V line voltage; No ballast or external driver required
Dimming Type	N/A
Power Factor	0.9
Operating Temperature	-25C (-13F) to a maximum of +45C (+113F)

**Physical**

MOL	48
MOD	1
Lens Finish	Frosted
Lens Material	Glass
Housing Color	White
Weight (lb.)	0.85

**Additional Information**

Additional Info	Installation protection - will not light if ballast is not bypassed.
Shatter-Proof Type	PET Coated
Installation Notes	Two Installation Options - 1. Double Ended Wiring or 2. Single Ended Wiring
Warranty	5 Year Limited - T8 LED Bulbs - Ballast Bypass

**Compliance**

Safety Listing	cULus Classified
Location Rating	Damp
Energy Star	No

DLC Approved	Yes
DLC ID	PLILPMGNF8VC
CEC Status	Lawful for sale in California
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	ETL Sanitation listed (conforms to NSF)

