

Project Name

Location

Prepared By



SATCO S11921

13.5T8/LED/48-835/DIM-BP

Notes

General

| | |
|----------------|---------------|
| Status | Active |
| Watts | 13.5 |
| Volts | 120V |
| Ballast Type | Type B |
| Shape | T8 |
| Base | Medium Bi Pin |
| ANSI Base | G13 |
| Nominal Length | 48 |
| Finish | Frosted |
| CCT (Kelvin) | 3500 |
| Temperature | Neutral White |
| CRI | 82 |
| Lumens | 1700 |
| Beam Spread | 220 |
| Dimmable | Yes Dimmable |
| Hours Rated | 50000 |
| Lamp Type | Linear |
| Technology | LED |

Electrical

| | |
|-------------------------|---|
| Ballasting Requirements | Ballast Bypass; Direct wire 120V line voltage; No ballast or external driver required |
| Power Factor | 0.9 |
| Operating Temperature | -20C (-4F) to a maximum of +45C (+113F) |

Physical

| | |
|---------------|---------|
| MOL | 48 |
| MOD | 1 |
| Lens Finish | Frosted |
| Lens Material | Glass |
| Housing Color | White |

Additional Information

| | |
|--------------------|--|
| Additional Info | All glass tube |
| Tube Guard Use | Approved for use with tube guards |
| Installation Notes | Install only in non-shunted lampholders |
| Warranty | 5 Year Limited - T8 LED Bulbs - Ballast Bypass |

Compliance

| | |
|-----------------|-------------------------------|
| Safety Listing | cULus Classified |
| Location Rating | Damp |
| Energy Star | No |
| DLC Approved | Yes |
| DLC ID | PL699Z8XDJKU |
| CEC Status | Lawful for sale in California |
| RoHS Compliant | Yes |
| FCC Compliant | Yes |

