

Project Name

Location

Prepared By



Notes

**General**

Status	Active
Watts	23
Fluorescent Equivalent	54
Volts	120V-277V
Ballast Type	Type C
Shape	T5
Base	Miniature Bi Pin
ANSI Base	G5
Nominal Length	48
Finish	Frosted
CCT (Kelvin)	3500
Temperature	Neutral White
CRI	82
Lumens	3400
Beam Spread	220
Dimmable	0-10V Dimming Only
Hours Rated	50000
Lamp Type	Linear
Technology	LED

**Electrical**

Ballasting Requirements	Ballast replaced with external driver
Operating Frequency	50/60 Hz
Power Factor	0.9
Operating Temperature	-20C (-4F) to a maximum of +45C (+113F)

**Physical**

MOL	48
MOD	0.63
Weight (lb.)	0.31

**Additional Information**

Additional Info	Not for emergency lighting
Warranty	5 Year Limited - 3 hr per day

**Compliance**

Safety Listing	cULus Classified
Location Rating	Damp
Energy Star	No
DLC Approved	Yes
DLC ID	PLQCYU7LBNEU
CEC Status	Lawful for sale in California
RoHS Compliant	Yes
NSF Approved	ETL Sanitation listed (conforms to NSF)

