

Project Name

Location

Prepared By



SATCO S13148

40HID/L/CCT3/E26/B/U

Notes

(www) 18-27-2023 05:20:07

General

Status	Active
Watts	40W/30W/20W
HID Equivalent	150W-175W
Volts	120V-277V
Shape	Corncob
Base	Medium
ANSI Base	E26
Finish	Clear
CCT (Kelvin)	3000K/4000K/5000K
Temperature	Soft White to Natural Light
CRI	80
Lumens	5800L-6400L/4350L-4800L/2900L-3200L
Beam Spread	120
Dimmable	Yes-Dimmable
Hours Rated	50000
Product Category	LED HID
Technology	LED
Ballasting Requirements	Ballast Bypass

Electrical

Operating Frequency	50/60Hz
Dimming Type	Step Dimming
Dimming Note	Only dimmable through wattage selection switch on lamp. NOT dimmable with wall dimmers or any other dimming controls.
Power Factor	>0.9
Operating Position	Base Down
Surge Protection	Built-in surge protection - 4KV
THD	<20%
Operating Temperature	-25C (-13F) to +50C (+122F)

Physical

MOL	5.68
MOD	5.69
Lens Finish	Translucent
Lens Material	Polycarbonate (PC)
Housing Color	White
Weight (lb.)	1.04

Additional Information

Rated For Enclosed Fixture	Yes
IP Rating	IP65
Warranty	5-Years

Compliance

Safety Listing	cULus
Location Rating	Wet
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp