

Project Name

Location

Prepared By



SATCO S13149

60HID/L/CCT3/EX39/B/U

Notes

(www) 18-27-2023 05:20:07

General

Status	Active
Watts	60W/45W/36W
HID Equivalent	200W-250W
Volts	120V-277V
Shape	Corncob
Base	Mogul Extended
ANSI Base	EX39
Finish	Clear
CCT (Kelvin)	3000K/4000K/5000K
Temperature	Soft White to Natural Light
CRI	80
Lumens	8700L-9600L/6525L-7200L/5220L-5760L
Beam Spread	120
Dimmable	Yes-Dimmable
Hours Rated	50000
Product Category	LED HID
Technology	LED
Ballasting Requirements	Ballast Bypass

Electrical

Operating Frequency	50/60Hz
Dimming Type	Step Dimming
Dimming Note	Only dimmable through wattage selection switch on lamp. NOT dimmable with wall dimmers or any other dimming controls.
Power Factor	>0.9
Operating Position	Base Down
Surge Protection	Built-in surge protection - 4KV
THD	<20%
Operating Temperature	-25C (-13F) to +50C (+122F)

Physical

MOL	6.57
MOD	6.63
Lens Finish	Translucent
Lens Material	Polycarbonate (PC)
Housing Color	White
Weight (lb.)	1.36

Additional Information

Rated For Enclosed Fixture	Yes
IP Rating	IP65
Warranty	5-Years

Compliance

Safety Listing	cULus
Location Rating	Wet
DLC Approved	Yes
DLC ID	S-2R1YW3
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp