

Project Name

Location

Prepared By



SATCO S21736

5.5G16/LED/CL/27K/E12/120V/2PK

Notes

General

| | |
|-------------------------|--------------|
| Status | Active |
| Watts | 5.5 |
| Incandescent Equivalent | 60 |
| Volts | 120V |
| Shape | G16 |
| Base | Candelabra |
| ANSI Base | E12 |
| Finish | Clear |
| CCT (Kelvin) | 2700 |
| Temperature | Warm White |
| CRI | 83 |
| Lumens | 500 |
| Beam Spread | 360 |
| Dimmable | Yes Dimmable |
| Hours Rated | 15000 |
| Lamp Type | Globe |
| Technology | LED |

Electrical

| | |
|-----------------------|--|
| Power Factor | 0.9 |
| Operating Temperature | -20C (-4F) to a maximum of +40C (104F) |

Physical

| | |
|-----|------|
| MOL | 3.24 |
| MOD | 2 |

Additional Information

| | |
|----------------------------|---------------------|
| Enclosure Rating | Enclosed Rated Lamp |
| Rated For Enclosed Fixture | Yes |
| Warranty | 3 Year Limited |

Compliance

| | |
|-----------------|---------------|
| Safety Listing | cULus |
| Location Rating | Damp |
| Energy Star | Yes |
| ES Unique ID | ESID-2348197 |
| CEC Status | Non-Compliant |
| RoHS Compliant | Yes |
| SDS Sheet | LED_Lamp |