

Project Name

Location

Prepared By



## SATCO S29900

9T8/LED/24-830/BP 120-277V

### Notes

#### General

Status	Active
Watts	9
Fluorescent Equivalent	17
Volts	120V-277V
Ballast Type	Type B
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	24
Finish	Frosted
CCT (Kelvin)	3000
Temperature	Warm White
CRI	82
Lumens	1100
Beam Spread	210
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Linear
Technology	LED

#### Electrical

Ballasting Requirements	Ballast Bypass
Dimming Type	N/A
Power Factor	0.9
Operating Temperature	-20C (-4F) to a maximum of +45C (+113F)

#### Physical

MOL	24
MOD	1
Weight (lb.)	0.24

#### Additional Information

Additional Info	All glass tube
Tube Guard Use	Approved for use with tube guards
Installation Notes	Existing wiring to both sockets can remain in place. Will work on both shunted or non-shunted sockets.
Specification Note	Built-in shock resistant circuit - (not hot until both ends are installed)
Warranty	5 Year Limited - T8 LED Bulbs - Ballast Bypass

#### Compliance

Safety Listing	cULus Classified
Location Rating	Damp
Energy Star	No
DLC Approved	Yes
DLC ID	PLQ28PR7FXG1
CEC Status	Lawful for sale in California
RoHS Compliant	Yes

