Project Name	
Location	Prepared By
	1
SSATCO sens	
SATCO S2 12T8/LED/48-835/DR-DM	29939

General	
Status	Transitioning
Watts	12
Fluorescent Equivalent	25W-32W
Ballast Type	Type A
Shape	Т8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48
Finish	Gloss
CCT (Kelvin)	3500
Temperature	Neutral White
CRI	82
Lumens	1700
Beam Spread	210
Dimmable	Check Ballast MFG for Dimmer Compatibility
Hours Rated	50000
Lamp Type	Linear
Technology	LED
Electrical	
	Ballast required. Direct Replacement- for use on Instant Start, Rapid Start, Emergency, an

Electrical	
Ballasting Requirements	Ballast required. Direct Replacement- for use on Instant Start, Rapid Start, Emergency, and Dimming ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatability chart.
Power Factor	0.9
Operating Temperature	-20C (-4F) to a maximum of +45C (+113F)

Physical	
MOL	48
MOD	1

Warranty	5 Year Limited - T8 LED Bulbs
Compliance	
Safety Listing	cULus
Location Rating	Damp
Energy Star	No
DLC Approved	No
CEC Status	Lawful for sale in California
RoHS Compliant	Yes

Notes

Additional Information









