SATCO NUVO

Project Name

Location

Prepared By



SATCO S9768

30W/LED/HID/MB/2700K/100-277V

Notes

[www] 12-07-2020 01:56:27

General	
	T
Status	Transitioning
Watts	30
Incandescent Equivalent	200
Fluorescent Equivalent	
HID Equivalent Volts	100V-277V
Shape	Corncob
Base	Medium
ANSI Base	E26
Finish	Clear
CCT (Kelvin)	2700
Temperature	Warm White
CRI	83
Lumens	3660
Beam Spread	360
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Corncob
Technology	LED
Min Compartment Size	Length: 11.02 in. Width: 8 in. Depth: 8 in.
Ballasting Requirements	Direct wire range voltage 100-277V
Electrical	
Working Voltage	AC 00 205V
Working Voltage	AC 90-305V
Operating Frequency	50-60 Hz
Operating Frequency Power Factor	50-60 Hz 0.9
Operating Frequency	50-60 Hz
Operating Frequency Power Factor	50-60 Hz 0.9 -20C (-4F) to a maximum of +65C
Operating Frequency Power Factor Operating Temperature Physical	50-60 Hz 0.9 -20C (-4F) to a maximum of +65C (+149F)
Operating Frequency Power Factor Operating Temperature Physical MOL	50-60 Hz 0.9 -20C (-4F) to a maximum of +65C (+149F)
Operating Frequency Power Factor Operating Temperature Physical MOL MOD	50-60 Hz 0.9 -20C (-4F) to a maximum of +65C (+149F) 6.38 3.19
Operating Frequency Power Factor Operating Temperature Physical MOL MOD Housing Color	50-60 Hz 0.9 -20C (-4F) to a maximum of +65C (+149F)
Operating Frequency Power Factor Operating Temperature Physical MOL MOD	50-60 Hz 0.9 -20C (-4F) to a maximum of +65C (+149F) 6.38 3.19
Operating Frequency Power Factor Operating Temperature Physical MOL MOD Housing Color	50-60 Hz 0.9 -20C (-4F) to a maximum of +65C (+149F) 6.38 3.19
Operating Frequency Power Factor Operating Temperature Physical MOL MOD Housing Color Additional Information	50-60 Hz 0.9 -20C (-4F) to a maximum of +65C (+149F) 6.38 3.19 White Width 360 deg 3.2 in.; Width 270
Operating Frequency Power Factor Operating Temperature Physical MOL MOD Housing Color Additional Information Additional Info	50-60 Hz 0.9 -20C (-4F) to a maximum of +65C (+149F) 6.38 3.19 White Width 360 deg 3.2 in.; Width 270 deg 6.8 in.; Width 180 deg 7.7 in.
Operating Frequency Power Factor Operating Temperature Physical MOL MOD Housing Color Additional Information Additional Info Rated For Enclosed Fixture	50-60 Hz 0.9 -20C (-4F) to a maximum of +65C (+149F) 6.38 3.19 White Width 360 deg 3.2 in.; Width 270 deg 6.8 in.; Width 180 deg 7.7 in. Yes
Operating Frequency Power Factor Operating Temperature Physical MOL MOD Housing Color Additional Information Additional Info Rated For Enclosed Fixture IP Rating	50-60 Hz 0.9 -20C (-4F) to a maximum of +65C (+149F) 6.38 3.19 White Width 360 deg 3.2 in.; Width 270 deg 6.8 in.; Width 180 deg 7.7 in. Yes IP65
Operating Frequency Power Factor Operating Temperature Physical MOL MOD Housing Color Additional Information Additional Info Rated For Enclosed Fixture IP Rating Warranty Compliance	50-60 Hz 0.9 -20C (-4F) to a maximum of +65C (+149F) 6.38 3.19 White Width 360 deg 3.2 in.; Width 270 deg 6.8 in.; Width 180 deg 7.7 in. Yes IP65 5 Year Limited - Hi-Pro
Operating Frequency Power Factor Operating Temperature Physical MOL MOD Housing Color Additional Information Additional Info Rated For Enclosed Fixture IP Rating Warranty Compliance Safety Listing	50-60 Hz 0.9 -20C (-4F) to a maximum of +65C (+149F) 6.38 3.19 White Width 360 deg 3.2 in.; Width 270 deg 6.8 in.; Width 180 deg 7.7 in. Yes IP65 5 Year Limited - Hi-Pro
Operating Frequency Power Factor Operating Temperature Physical MOL MOD Housing Color Additional Information Additional Info Rated For Enclosed Fixture IP Rating Warranty Compliance Safety Listing Location Rating	50-60 Hz 0.9 -20C (-4F) to a maximum of +65C (+149F) 6.38 3.19 White Width 360 deg 3.2 in.; Width 270 deg 6.8 in.; Width 180 deg 7.7 in. Yes IP65 5 Year Limited - Hi-Pro cULus Damp
Operating Frequency Power Factor Operating Temperature Physical MOL MOD Housing Color Additional Information Additional Info Rated For Enclosed Fixture IP Rating Warranty Compliance Safety Listing Location Rating Energy Star	50-60 Hz 0.9 -20C (-4F) to a maximum of +65C (+149F) 6.38 3.19 White Width 360 deg 3.2 in.; Width 270 deg 6.8 in.; Width 180 deg 7.7 in. Yes IP65 5 Year Limited - Hi-Pro CULus Damp No
Operating Frequency Power Factor Operating Temperature Physical MOL MOD Housing Color Additional Information Additional Info Rated For Enclosed Fixture IP Rating Warranty Compliance Safety Listing Location Rating	50-60 Hz 0.9 -20C (-4F) to a maximum of +65C (+149F) 6.38 3.19 White Width 360 deg 3.2 in.; Width 270 deg 6.8 in.; Width 180 deg 7.7 in. Yes IP65 5 Year Limited - Hi-Pro cULus Damp
Operating Frequency Power Factor Operating Temperature Physical MOL MOD Housing Color Additional Information Additional Info Rated For Enclosed Fixture IP Rating Warranty Compliance Safety Listing Location Rating Energy Star California Status	50-60 Hz 0.9 -20C (-4F) to a maximum of +65C (+149F) 6.38 3.19 White Width 360 deg 3.2 in.; Width 270 deg 6.8 in.; Width 180 deg 7.7 in. Yes IP65 5 Year Limited - Hi-Pro CULus Damp No Lawful for sale in California

SDS Sheet





LED_Lamp













