

Ballast Type	Туре В	
Shape	Т8	
Base	Recessed Double Contact HO/VHO	
ANSI Base	R17d	
Nominal Length	96	
Finish	Gloss White	
CCT (Kelvin)	5000	
Temperature	Natural Light	
CRI	82	
Lumens	5500	
Beam Spread	210	
Dimmable	Non-Dimmable	
Hours Rated	50000	
Lamp Type	Linear	
Technology	LED	
Electrical		
Ballasting Requirements	Ballast Bypass	
Operating Frequency	50/60 Hz	
Dimming Type	N/A	
Operating Temperature	-20C (-4F) to a maximum of +45C (+113F)	
Physical		
MOL	96	
MOD	1	
Additional Information		
Shatter-Proof Type	Yes	
Installation Notes	Double ended wiring	
Warranty	5 Year Limited - T8 LED Bulbs - Ballast Bypass	
Compliance		

Active

43

110

120V-277V

arranty
compliance
afety Listing
tion Rating
3

General

Safety Listing	cULus Classified	
Location Rating	Damp	
Energy Star	No	
CEC Status	Lawful for sale in California	
RoHS Compliant	Yes	
NSF Approved	Yes - Approved	

43T8/LED/96-850/BP/R17D HO

Notes







