

Project:

Purolinear 360 LED Wall Bar Spec Sheet

SKU: 23QSKN222R120PHA Learn more at:
<https://sonnemanlight.com/purolinear-360-led-wall-bar>

Description: A system of linear tubes, set within the geometry of surface-mounted cylinder brackets, rotate individually to direct the LED illumination in 360 degrees along their axis. Arranged in a linear pattern or along a single path, the possibilities for compositions are endless and unlimited in scalability. Set on a wall, in line behind a bed, the rotatable luminaires provide the variability of direct or indirect illumination.

Type #:



Dimensions

Height:	24.75"
Width:	49.25"
Extends:	2.75"
Minimum Extension:	2.75"
Maximum Extension:	2.75"
Shape:	Double N
Size:	24"

Installation

Installation:	Licensed electrician required
---------------	-------------------------------

Shade

Shade 1 Material:	Optical Acrylic
-------------------	-----------------

General Listings

Features:	ADA Compliant, Damp Rated
Certification:	C-ETL-US
Color/Finish:	Satin Black (.25)
Dark Sky Friendly:	N

Electrical Specs

Bulb(s) Included?:	Yes
Bulb 1 Type:	Integral LED
Bulb Quantity:	4
Input Voltage:	100-277VAC
Wattage:	7
Initial Lumens:	2760
Delivered Lumens:	1960
Color Temperature:	3000K
CRI:	90
Power Supply Type:	Driver
Power Supply Quantity:	1
Power Supply Location:	Remote
Dimming Type:	TRIAC/ELV/0-10V
Bulb Max Wattage:	7

Available Finishes

Available Finishes: Polished Chrome (.01), Satin Black (.25), Satin Chrome (.23), Satin White (.03)