



**Accord®**  
60" ADA seated bath  
71141114



**Features**

- 17-1/4 (438 mm) apron.
- Bath seat on right.
- Must be installed with Accord wall set (71144113, 71144123, 71244113 or 71244123)

**Material**

- Made from solid Vikrell® material for strength, durability, and lasting beauty.

**Installation**

- Alcove.
- Left drain.

**Recommended Products/Accessories**

- K-23726 Drain treatment
- K-23733 Vikrell® cleaner



**ADA**

**Codes/Standards**



- CSA B45.5/IAPMO Z124
- ASTM E162
- ASTM E662
- ADA

**Warranty – Bathing Fixtures (and)  
Kitchen and Utility Sinks Made of  
Solid Vikrell® Material**  
**STERLING®  
Warranty - Bathing & Showering  
Seats**

See website for detailed warranty information.

**Available Colors/Finishes**

*Color tiles intended for reference only.*

Color	Code	Description
	0	White
	96	KOHLER Biscuit

1-800-STERLING (1-800-783-7546)

Kohler Co. reserves the right to make revisions without notice to product specifications.

For the most current Specification Sheet, go to [www.sterlingplumbing.com](http://www.sterlingplumbing.com).

5-29-2021 07:30 - US/CA



**Accord®**  
60" ADA seated bath  
**71141114**

No image available.  
This product is a component and not intended to be a standalone installation.

### Technical Information

All product dimensions are nominal.

Installation:	Three-wall alcove
Drain location:	Left
Basin area, bottom:	46-1/4" x 20-1/2" (1175 mm x 521 mm)
Basin area, top:	52-1/4" x 22-1/2" (1327 mm x 572 mm)
Maximum door width:	56-1/2" (1435 mm)

### Notes

Install this product according to the installation instructions.

Product is designed to be used with a single-hole mixer valve with an escutcheon cover not to exceed 7-3/4" (197 mm) in width.

Bath cannot be installed without the wall surround.

Width of back wall at top transitions from 60" (1524 mm) at the front to 59-3/8" (1508 mm) in the back corners. Furring strips approximately 1/4" (6 mm) thick should be used at the back corner studs if drywall is to be installed over the nailing flange.

ADA compliant when installed to the specific requirements of these regulations.