

QURC-3322 Granite Undermount Offset Double Bowl Kitchen Sink


Manufactured from Quartz

WARRANTY Limited Lifetime – Residential Limited 10-year – Commercial

(See page 2 for detailed information.)

FEATURES

- Made with 80% quartz stone, only a diamond is harder.
- Virtually indestructible, will not damage from kitchen use.
- Standard sink size.
- Ideal for remodeling or new construction.
- Mounts under most countertop materials including granite, quartz, solid surface and tile.



SPECIFICATIONS

QURC-3322 Granite Undermount Offset Double Bowl Kitchen Sink

Model	Part	Nominal Dimensions	Ship Wt. Lb.	- F	Carton Dims. In.	Cu. Ft.
QURC-3322	QU03322RC	32" W x 21" D (813 mm x 533 mm)	48	FedEx	37 x 25 x 13	6.96

$\begin{array}{c} & 11^{1/4"} \longrightarrow 11^{1/2"} \longrightarrow \\ & 3^{13/16"} \longrightarrow \\ & 18^{3/16"} \longrightarrow \\ & 18^{3/16"} \longrightarrow \\ & 16^{1/32"} \longrightarrow \\ & 13^{3/16"} \longrightarrow \\ & 13^{3/16"} \longrightarrow \\ & 32" \longrightarrow \end{array}$

Capacity: 11 gallons in large (left) bowl, and 7-1/4 gallons in small (right) bowl

COLORS

(See inside back cover for color sample.)

- Espresso (170)
- Granito (076)
- Metallico (173)
- Nero (077)

MAINTENANCE AND CLEANING INFORMATION

Clean your Swan Granite Sink by using warm water and a soft clean cloth, or sponge. Non-abrasive liquid cleaners and detergents can also be used. Hard water, calcium and lime deposits can be removed with white vinegar on a paper towel and rinsing after 20 minutes. To restore luster and extend time between cleanings Granite Cleaner & Polish is recommended. Staining liquids, such as dyes and vegetable juices should be rinsed off as soon as possible. **Do not** use abrasive cleaners, metal-scouring pads, and bleach or alkali cleaners, such as ammonia.

STANDARDS AND RATINGS

American National Standard Institute—ANSI Z124.6 International Association of Plumbing and Mechanical Officials (IAPMO) – listed cUPC listed – Certified to CSA Standard B45 by IAPMO Heat resistance to 392°F, 200°C

SUPPORT DOCUMENTS

Installation instructions available at swanstone.com.

Undermount clips sold separately. Faucet options are limited to available hole placement. Please contact your dealer for more information.