

## QUSQ-3322 Granite Undermount Equal Double Bowl Kitchen Sink


Recommended for high-use traffic areas and commercial surfaces.

### **Manufactured from Quartz** (See page 2 for detailed information.)

WARRANTY Limited Lifetime – Residential Limited 10-year – Commercial

# FEATURES

- Made with 80% quartz stone, only a diamond is harder.
- Virtually indestructible, will not damage from kitchen use.
- Standard sink size.
- Ideal for remodeling or new construction.
- Mounts under most countertop materials including granite, quartz, solid surface and tile.



# SPECIFICATIONS

## QUSQ-3322 Granite Undermount Equal Double Bowl Kitchen Sink

Model	Part	Nominal Dimensions	Ship Wt. Lb.	Ship FedEx	Carton Dims. In.	Cu. Ft.
QUSQ-3322	QU03322SQ	32" W x 21" D (813 mm x 533 mm)	48	FedEx	37 X 25 X 13	6.96

# $\begin{array}{c} & 8^{7}/16^{n} & & 15^{1}/6^{n} \\ \hline \\ 19^{1}/4^{n} \\ \downarrow \\ 16^{3}/6^{n} \\ \hline \\ 13^{7}/6^{n} \\ \hline \\ 13^{7}/6^{n} \\ \hline \\ 31^{7}/8^{n} \\ \hline \\ 31^{7}/8^{n} \\ \hline \end{array} \right)$

Capacity: 8-1/2 gallons per each bowl

# COLORS

(See inside back cover for color sample.)

.....

- Espresso (170)
- Granito (076)
- Metallico (173)
- Nero (077)

## MAINTENANCE AND CLEANING INFORMATION

Clean your Swan Granite Sink by using warm water and a soft clean cloth, or sponge. Non-abrasive liquid cleaners and detergents can also be used. Hard water, calcium and lime deposits can be removed with white vinegar on a paper towel and rinsing after 20 minutes. To restore luster and extend time between cleanings Granite Cleaner & Polish is recommended. Staining liquids, such as dyes and vegetable juices should be rinsed off as soon as possible. **Do not** use abrasive cleaners, metal-scouring pads, and bleach or alkali cleaners, such as ammonia.

Undermount clips sold separately. Faucet options are

limited to available hole placement. Please contact

your dealer for more information.

## STANDARDS AND RATINGS

American National Standard Institute—ANSI Z124.6 International Association of Plumbing and Mechanical Officials (IAPMO) – listed cUPC listed – Certified to CSA Standard B45 by IAPMO Heat resistance to 392°F, 200°C

## SUPPORT DOCUMENTS

Installation instructions available at swanstone.com.

Swan • (800)325-7008 • swanstone.com • help@swanstone.com