GALVANIZED STUB OUT BRACKET

>> 521-3725B

SPECIFICATION

Sioux Chief's galvanized stub out bracket shall be used where necessary to support $\frac{1}{2}$ ", $\frac{3}{4}$ " or 1" nominal stub outs for water supply lines. Bracket shall be made from heavy-gauge, galvanized steel. Bracket design shall include holes to fit Sioux Chief PipeEye metal stud insulators or other types of plastic insulators that fit the pipe hole I.D. on the bracket.

INSTALLATION

Using approved hardware, secure bracket with nail or screw to stud or base plate through any pre-drilled pilot hole. Insert stub out into pipe hole. Open plastic grommet to fit around pipe then push plastic grommet through the bracket. Molded ears on backside of grommet are designed to hold grommet in place.

MATERIAL

14-gauge galvanized steel (.0737" metal thickness)

MAXIMUM LOAD RATING

25 lbs.

DIMENSIONS


A: width 2" B: height 3" C: foot length 13/4" D: number of pipe holes 2

E: distance between pipe holes 2" on-center F: outside diameter of pipe hole 111/32" G: nail hole diameter .187"

ITEM # SUBMITTED
JOB NAME
LOCATION
ENGINEER
CONTRACTOR
PO# TAG



521-3725B





Item Number

521-3725B