

# ACOUSTICAL NOISE BLOCK FOR UNIVERSAL PIPE CLAMP

»» 522 SERIES

PipeDown™ TouchDown™

## SPECIFICATION

Sioux Chief 522 Series acoustical noise blocks for TouchDown™ Universal Pipe Clamps shall be used where necessary to reduce noise caused by thermal expansion/contraction or vibration of water supply lines in residential or commercial applications. Noise blocks shall not alter head or weight tolerances. Noise blocks shall not be used with plenum-safe TouchDown™ clamp models. Noise blocks shall be UPC/IAPMO certified.

## INSTALLATION

Install universal pipe clamp (purchased separately) with screw to stud, joist, or other structure surface. Insert one noise block into each clamp base and bridge. Lay tube or pipe in base of clamp and ratchet bridge evenly over pipe to secure.

## MATERIALS

TPE, shore A 38

## SAFE WORKING TEMPERATURE

180°F (82°C)


## DIMENSIONS

**A:** Width 0.97"  
**B:** Height 0.42"

ITEM # SUBMITTED	_____
JOB NAME	_____
LOCATION	_____
ENGINEER	_____
CONTRACTOR	_____
PO#	_____ TAG _____



522-100B



Made in USA

Item Number

522-100B