# DWV PIPE SUPPORT

>> 523-712W & 523-734W

Combo Saddle

#### **SPECIFICATION**

Sioux Chief's ComboSaddle™ DWV pipe support shall be used where necessary to support Schedule 40 DWV piping on residential single family and multi-family projects. Pipe support cradle shall be designed to flex so that each model number supports two different pipe sizes for pipes ranging from 1½" through 4". Pipe support shall be secured to PowerBar™ Universal Slider bracket with approved hardware (provided). Pipe support shall be IAPMO certified.

## **INSTALLATION**

Follow national code requirements for proper pipe slope, when applicable. Secure galvanized PowerBar<sup>™</sup> bracket (purchased separately) between studs or joists using all four tabs with screws. Position cradle around pipe either vertically or horizontally and secure pipe support to galvanized bracket. If desired, apply multi-purpose glue to pipe support. Acceptable installations include vent riser clamp applications on plastic pipe within stud walls.

#### **MATERIALS**

ComboSaddle: ABS, U.V. resistant, corrosion proof, impact resistant Screw: #8 x 1" phillips pan-head with drill tip

## SAFE WORKING LOAD

25 lbs.


## **DIMENSIONS**

	523-712W	523-734W
A: Saddle Clamp base height	.80"	.80"
B: Cradle diameter	1.88"	3.5"
C: Screw length	1"	1"





523-712W





Made in USA

**Choose Item Number** 

523-7A

e.g. 523-712W: ComboSaddle<sup>TM</sup> for  $1\frac{1}{2}$ " - 2" DWV pipe

**CRADLE SIZE A** 

**12W** = 1½" - 2" DWV pipe 34W = 3" - 4" DWV pipe