

# ACOUSTICAL SELF-ADHESIVE PIPE WRAP

» 575-102Q

PipeDown™ Pipe Wrap

## SPECIFICATION

Sioux Chief's acoustical pipe wrap shall be used when job specifications call for acoustical pipe support products to help reduce noise levels in piping systems. Pipe Wrap material and self-adhesive strips shall be compatible with copper, PEX and CPVC. Pipe wrap shall be certified by UPC/IAPMO.

## INSTALLATION

1. Cut wrap to desired length.
  2. Remove paper strip to expose adhesive.
  3. Apply adhesive side to pipe and wrap pipe fully.
  4. Secure pipe in clevis hanger, strut clamp or other clamp or hanger per hanger manufacturer's instructions.
- Overlapping the material is acceptable. Trim material down the center to narrow the strip when necessary.

## MATERIAL

TPE shore A35

## TEMPERATURE RANGE

-30°F – 180°F


## DIMENSIONS

A: Width	2.01"
B: Thickness	0.228"
C: Width of adhesive strip (x2)	0.551"
D: Length	25 ft.

ITEM # SUBMITTED	_____
JOB NAME	_____
LOCATION	_____
ENGINEER	_____
CONTRACTOR	_____
PO#	_____ TAG _____



575-102Q



Made in Taiwan

Item Number

**575-102Q**