

# BLACK VINYL TUBING

## ▶▶ POLYVINYL CHLORIDE

### ATTRIBUTES

Sioux Chief black vinyl tubing is manufactured to specifications from FDA listed polyvinyl chloride material. Tubing has a smooth, dense bore for maximum flow and reduced sediment buildup. Tubing is resistant to U.V., ozone and many gases, acids, alkalis, and chemicals (see website for chemical resistance listing).

**Operating temperature range:** -40°F (-40°C) to 125°F (52°C)

**Brittle point:** -40°F (-40°C)

**Material:** Polyvinyl chloride

**Color:** Black

**Hardness:** Durometer 83+/-3 Shore A

### APPLICATIONS

Cooler supply lines, Drainage lines, protective insulation in water gardens, fish tanks

⚠ **WARNING: Not intended for use on ice maker and dishwasher applications.**

### PRESSURE RANGE

I.D.	O.D.	WALL	WORKING PRESSURE (PSI @70°F)
.170"	¼"	.040"	55
¼"	⅜"	⅙"	55
⅜"	½"	⅙"	45
½"	⅝"	⅙"	45
⅝"	¾"	⅙"	30
¾"	1"	⅙"	35
1"	1¼"	⅙"	25
⅜"	½"	⅙"	55
⅜"	⅝"	⅙"	55
⅜"	⅞"	⅙"	55

ITEM # SUBMITTED	_____
JOB NAME	_____
LOCATION	_____
ENGINEER	_____
CONTRACTOR	_____
PO#	_____ TAG _____



NSF/ANSI 61 Compliant  
NSF/ANSI 51 Compliant



### Create Item Number

## 900-01A B N C D

e.g. 900-01253N01005: Black vinyl tube, ⅝" ID × ¾" OD (⅙" Wall), 100ft dispenser box

#### ID SIZE A

**03** = 17/100"  
**10** = ¼"  
**16** = ⅜"  
**20** = ½"  
**25** = ⅝"  
**30** = ¾"  
**40** = 1"

#### WALL B

**0** = Misc  
**3** = ⅙"  
**6** = ⅙"

#### LENGTH C

**0010** = 10ft  
**0020** = 20ft  
**0050** = 50ft  
**0100** = 100ft

#### PACKAGE D

**1** = Coils  
**3** = EZ dispenser boxes  
**5** = Reels

\*Not all size, wall thickness and length combinations available. Contact your local rep to confirm availability.