

Location:



# SYMMONS® Museo®

## Shower System 5301

### Specification Submittal



#### Feature Highlights

- Symmons Shower System with lever handle
- Symmons Temptrol® pressure-balancing mixing valve with adjustable stop screw to limit handle turn
- Showerhead #532SH, single mode, 5-3/4 inch diameter
- Showerhead mounting bracket and flange
- Standard flow rate is 2.5 gpm (9.5 L/min)  
*Optional lower flow rate restrictor available*
- Polished chrome finish (standard)

#### Model Numbers

- 5301  
Shower System with Symmons Temptrol mixing valve  
p/n 46-2-BODY
- 5301-TRM  
Trim only, valve must be ordered separately
- 46-2-BODY  
Symmons Temptrol mixing valve without trim
- 46-2X-BODY  
Symmons Temptrol mixing valve without trim.  
Valve includes integral service stops

#### Finish Options / Modifications

*Append appropriate -suffix to model number*

- STN Satin nickel
- BLK Polished graphite
- Polished chrome (standard finish)

#### Warranty

- Limited Lifetime - to the original end purchaser in consumer installations
- 5 years - for commercial installations



#### Standards / Certifications

ASME A112.18.1/CSA B125.1



#### Options / Modifications

*Append appropriate -suffix to model number*

-  -1.5 1.5 gpm (5.7 L/min) flow restrictor
- 2.0 2.0 gpm (7.6 L/min) flow restrictor
- IPS 1/2" female IPS connections
-  -LP Loop handle
- L/HD Less showerhead
- REB Rebuild trim kit, includes TA-10 and TA-4
- REV Reverse coring, hot on right, cold on left, for back to back installations
- VP Vandal resistant escutcheon screws in place of standard screws
- X Integral service stops - allows water shutoff at valve for service
- X-CHKS Integral check stops - for use in installations where a positive shut-off device is used downstream of mixing valve

## Dimensions Museo Shower System, 5301

